



Conductivity measuring cell $c = 0.1 \text{ cm}^{-1}$ with Pt1000 (fixed cable)

6.0918.040

Conductivity measuring cell made of stainless steel with cell constant $c = 0.1 \text{ cm}^{-1}$ (guide value), with integrated Pt1000 temperature sensor and fixed cable for connecting to 912/914 Meters. This sensor is suitable for measurements of low conductivities ($0 \text{ }\mu\text{S/cm}$ to $300 \text{ }\mu\text{S/cm}$) in, e.g. deion. water.

Below, the accessories are grouped into Scope of delivery and Optional accessories. Please keep this printout at hand for ordering replacement material. These lists may be subject to change.

Scope of delivery 6.0918.040

Qt.	Order no.	Description
-----	-----------	-------------

1 PCS

6.1236.050

Sleeve with SGJ 14/12 mm

Sleeve with SGJ 14/12 mm, polyethylene.



Optional accessories

Order no.	Description
-----------	-------------

6.1420.100 Flow-through measuring vessel
For 12 mm dia. electrodes (pH, metal, conductivity)



6.2324.010 Conductivity standard 100 µS/cm 250 mL
Conductivity standard for calibration of conductivity measuring cells with cell constant = 0.1/cm.



6.2324.110 Conductivity standard 100 µS/cm, 5 x 30 mL
Conductivity standard for calibration of conductivity measuring cells with cell constant = 0.1/cm.

